**Image Scanner** 

# RICOH imagine. change.

## RICOH fi-7700 Datasheet

☑ Scanner



### Flatbed scanner for professional use enables heavy-duty & flexible scanning

The fi-7700 scans documents at 100 ppm/200 ipm (A4 landscape 200/300 dpi) and improves work efficiency with its ability to scan a wide variety of business documents as well as capacity to load 300 sheets at a time.

#### Assistance for safe and reliable scanning

The straight paper path structure is designed to assure stable scanning regardless of document conditions and types. With Manual/Single mode, scan thick documents such as drawings folded in half, multi-layered receipts, and envelopes without specific operation. Minimize risk of document damage with stable paper feeding that Paper Protection function provides through its detection of anomalies in sound and monitoring of paper feed distance. Missing edges are also no longer a struggle with the scanner's Skew Reducer mechanism.

#### Flexible and functional design to meet all user needs

The fi-7700 is equipped with an ADF that can slide to the right or left, as well as rotate 180 degrees, enabling easy document loading with ADF adjustment to suit workspace environments or physical conditions.

Keep track of scanner operations such as document scanning settings, number of sheets scanned, as well as any existing error statuses, using the LCD operation panels. Load documents with ease and reduce your workload before and after scanning, with the scanner's independent side guides helping you align edges of variously sized documents. You can now also scan thick or fragile documents with the document cover kept open, thanks to the Cover-Open Cropping function.

#### Advanced software for maximized efficiency

Bypass the inconvenience of making fine adjustments to OCR settings with the PaperStream IP scanner driver, supporting both TWAIN and ISIS. The software automatically converts scanned images into exceptionally clean images, supporting OCR accuracy even when scanning documents with background patterns or wrinkled and soiled documents. Seamlessly linked to PaperStream IP, PaperStream Capture effectively and efficiently feeds information into your organization workflow with its various batch scanning capture features. Automatically utilizing data extracted from barcodes and patch codes, the software also determines your preferred saving destinations and eliminates time allocated to routine tasks.

#### RICOH fi-7700

#### **Technical Information**

echnical inform	iatioi	I		
Scanner Type		ADF (Automatic Document Feeder) / Manual Feed /		
		Flatbed, Duplex		
Scanning Speed*1	(A4 Lar	ndscape) (Color*²/Grayscale*²/Monochrome*³)		
ADF		Simplex: 100 ppm (200/300 dpi)		
		Duplex : 200 ipm (200/300 dpi)		
		0.6 seconds (200/300 dpi)		
Scanning Speed*1	(A4 Por	rtrait) (Color*²/Grayscale*²/Monochrome*³)		
ADF		Simplex: 80 ppm (200/300 dpi)		
		Duplex : 160 ipm (200/300 dpi)		
Flatbed		0.9 seconds (200/300 dpi)		
Image Sensor Type		Color CCD x 3 (front x 1, back x 1, Flatbed x 1)		
Light Source		White LED Array x 6 (front x 2, back x 2, Flatbed x 2)		
Optical Resolution		600 dpi		
Output Resolution		, 555 Gp.		
(Color / Grayscale		50 to 600 dpi (adjustable by 1 dpi increments),		
(Color / Grayscale / Monochrome)		1,200 dpi (driver)*5		
Output Format		Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit		
Background Color	c	ADF: White / Black (selectable)		
background color	,	, , , ,		
Document Size		Flatbed: White (or optional black)		
ADF Maximum		304.8 x 431.8 mm (12 x 17 in.)		
Minin				
		50.8 x 69 mm (2 x 2.7 in.) (Portrait)		
Long	-	5,588 mm (220 in.)		
	ning* <sup>6</sup>	204.0 457.2 (42 40 :- )		
Flatbed Maxir		304.8 x 457.2 mm (12 x 18 in.)		
Paper Weight (Thi	ckness)			
Paper		20 to 413 g/m² (5.3 to 110 lb)		
		Less than A8 size: 128 to 209 g/m² (34 to 56 lb)		
Plastic Card		Up to 1.4 mm*8		
ADF Capacity*9		300 sheets (A4 80 g/m² or Letter 20 lb)		
Expected Daily		44,000 sheets		
Volume*10				
Multifeed Detection		Overlap detection (Ultrasonic sensor),		
		Length detection		
Paper Protection		Lag detection, Sound detection (iSOP)*11		
Interface		USB 3.1 Gen1 / USB 2.0 / USB 1.1		
Power Requirements		AC 100 to 240 V ±10 %		
Power Consumption	on			
Operating Mode Sleep Mode		64 W or less		
		1.7 W or less		
Auto Standby (Off) Mode		0.3 W or less		

Operating Environment		
Temperature	5 to 35 °C (41 to 95 °F)	
Relative Humidity	20 to 80% (non-condensing)	
Environmental	ENERGY STAR®, RoHS	
Compliance		
Dimensions*12		
(Width x Depth x	706 x 500 x 345 mm (27.8 x 19.7 x 13.6 in.)	
Height)		
Weight	35 kg (77 lb)	
Supported	Windows 11*13, Windows 10*13, Windows Server	
Operating System	2025, Windows Server 2022, Windows Server 2019,	
	Windows Server 2016	
Software / Drivers*15	PaperStream IP driver (TWAIN/TWAIN x64/ISIS),	
	WIA Driver*14, PaperStream Capture, PaperStream	
	ClickScan, Software Operation Panel, Error Recovery	
	Guide, ABBYY FineReader for ScanSnap™,	
	PaperStream Central Admin	
Image Processing	Multi image output, Automatic color detection, Blank	
Functions	page detection, Dynamic threshold (iDTC), Advanced	
	DTC, SDTC, Error diffusion, Dither, De-Screen,	
	Emphasis, Dropout color (None/Red/Green/Blue/	
	White/Saturation/Custom), sRGB output, Hole punch	
	removal, Index tab cropping, Split image, De-Skew,	
	Edge correction, Vertical streaks reduction, Cropping,	
	Static threshold, Divide long page	
Included Items	Stacker, ADF paper chute, AC cable, AC adapter,	
	USB cable, Setup DVD-ROM	

#### Options

95.00.0					
Black Document Pad	D4 022220 D060	Black flatbed background pad			
(FI-575BK)	PA03338-D960				
PaperStream Capture Pro		One year license of PaperStream			
Premium	PA43404-B421	Capture Pro Premium			

#### Consumables

Consumables					
	Brake Roller	PA03740-K010	Every 250,000 sheets*16		
	Pick Roller	PA03740-K011	Every 250,000 sheets*16		

\*1 Scanning speeds may vary due to the system environment. For details, please visit our website at: https://www.pfu.ricoh.com/global/scanners/fi/. \*2 Indicated speeds are from using JPEG compression.
\*3 Indicated speeds are from using TIFF CCITT Group 4 compression. \*4 Selectable maximum resolution may vary depending on the length of the scanned document. \*5 Limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). \*6 Capable of scanning documents that exceed Legal sheets in length. Long page scanning supports documents with lengths of up to 5,588 mm (220 in.) when the resolution is set to 200 dpi or less. Documents of up to 200m (218.8 yd.) can be scanned if scans of long page documents are split into multiple pages. \*7 Paper weight limitations only apply when using the ADF. There are no limitations when using the flatbed. \*8 Capable of scanning up to 3 cards at a time when using the ADF. (Note: only one embossed card can be scanned at a time). \*9 Maximum capacity depends on paper weight and may vary. \*10 Numbers are calculated using scanning speeds and typical hours of scanner use, and are not meant to guarantee daily volume or unit durability. \*11 Intelligent Sonic Paper Protection. \*12 Excludes the ADF hopper and stacker. \*13 fi Series scanners do not run with Windows 11 and 10 ARM-based PCs. \*14 Functions equivalent to those offered by PaperStream IP may not be available with the WIA Driver. \*15 Refer to the fi Series Support Site for driver/software downloads and full lineup of all supported operating system versions. \*16 Replacement cycles are guidelines for using A4 documents (80 g/m² [20 lb]). These cycles vary depending on the type of documents scanned, how often the scanner is used and cleaned, and your operating environment.

#### Trademarks

ABBYYTM FineReader TM Engine © ABBYY. OCR by ABBYY. ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are trademarks of the Microsoft group of companies. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

Safety Precautions

Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings.

ENERGY STAR®

PFU Limited has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

### **PFU Limited**

RICOH and RICOH logo are registered trademarks of Ricoh Co., Ltd. Other product names are the trademarks or registered trademarks of the respective companies.

Specifications are subject to change without notice. Visit the fi Series website for more information. https://www.pfu.ricoh.com/global/scanners/ © PFU Limited 2025

https://www.pfu.ricoh.com/global/

Page 2 of 2 2025.01 7700-9.0